

SUpport to SAfety ANalysis of Hydrogen and Fuel Cell Technologies

Verification type	Sensitivity Studies (Grid and Parameter sensitivity)
Database reference	SEN-4
Topic / Application	Nuclear Safety
	Verification and Validation
Physics	Boron Dilution Transient
Summary	Presents an identification and ranking of the main physical phenomena in a nuclear safety simulation, to inform appropriate use of codes.
Description	The representation of application and validation domains has been studied by the authors . Though the application is validation the processes for identifying and ranking physics can be applied to verification, where the ranking is applies to the equivalent mathematical terms in the equations to be solved, ensuring that errors in small terms are not swamped by larger terms. The representation of application and validation domains has been studied by the authors. For each physical phenomenon identified, dimensionless numbers are used to evaluate the ratio of parameters of strong influence. Every validation test or industrial application can thus be plotted and defined by a range of values for dimensionless numbers. The relevance of domains representation is thus based on the confidence in the physical analysis.
Case Title	USING THE PIRT TO REPRESENT APPLICATION AND VALIDATION DOMAINS FOR CFD STUDIES
Authors	B. Gaudron1, H. Cordier1, S. Bellet1, D. Monfort2
Year	
Online reference	bruno.gaudron@edf.fr

The SUSANA project is co-funded by the European Commission within the 7th Framework Program





SUpport to SAfety ANalysis of Hydrogen and Fuel Cell Technologies